

LOWRY'S BOX PADS

Outlet Box Pads To Reduce Transmitted Air and Sound



BEFORE



AFTER



BEFORE



AFTER

BASIC USES:

Lowry's electrical box pads are used to seal the back side of electrical boxes, TV jack boxes and telephone outlet boxes to reduce air and sound transmission in shared walls.

LIMITATIONS:

- Do not use in areas subjected to constant heat above 200 degrees F
- Not to be used in areas requiring a fire rating.
- Do not expose to flame

PACKAGING:

144 -1/8" x 6" x 8" pads per case

COLOR:

Putty Gray only

APPLICATION METHODS:

Preparation:

- 1) Properly clean substrate removing dust or debris from the surface to be applied.
- 2) If surface is contaminated with oil or other residue, clean with a solvent wipe followed with a dry rag wipe.

Application:

- 1) After the box installation is completed, remove Lowry pad from carton and place the pad centered on the back of the box. Carefully mold and fold around conduit cable entering box.
- 2) Remove paper backing
- 3) Retrofit boxes will need to have the pad applied before the box is put in place. *Do not apply to the inside of the box.*

Note: After drywall or plaster is completed, it may be necessary to complete a perimeter seal with a gun able acoustical sealant between the dry wall and the box in order to create a true sound air barrier. The pad's function is to easily seal nail and knockout holes in boxes to prevent air transmission and sound transmission.

AVAILABILITY:

Immediately available from multiple Lowry's Inc. locations and most construction, plumbing and electrical supply distributors.

COMPOSITION:

Polybutene-butyl, inert fillers. (No asbestos)

TECHNICAL DATA	
SHELF LIFE	1 YEAR
SOLIDS	100%
SERVICE TEMP	-30 TO 200 F
ADHESION	GOOD TO METAL AND PLASTIC

LIMITED WARRANTY: We warranty our products to be free of defects and manufactured to meet published physical properties. We will provide, at no charge, product to replace any product proved to be defective when applied in accordance with our written instructions. All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will constitute a waiver of all claims with respect of said product. This warranty is in lieu of any and all other warranties expressed or implied. **PLEASE NOTE: Lowry's Pads and Wrap have been grandfathered through our organization for decades. There has never been any registered testing for sound transmission or fire resistance.**

LOS ANGELES – 8501 Telfair Ave. Sun Valley, CA 91352 Phone: (800) 225-8231 (818) 768 4661 Fax: (818) 768-4130

ORANGE COUNTY – 721 S Van Buren St. Placentia, CA 92870 Phone: (800) 439-4546 (714) 777-1172 Fax: (714) 777-2099

BAY AREA – 23030 Kidder St. Hayward, CA 94545 Phone: (800) 252-2449 (510) 785-2404 Fax: (510) 785-2405

SACRAMENTO – 1556 Santa Ana Ave Suite 120, Sacramento, Ca Phone: (866) 270-7333 (916) 372-7333 Fax: (916) 372-7305

SAN DIEGO – 8840 Complex Dr. San Diego, CA 92123 Phone: (858) 430-1260 Fax: (858) 268-9662

PHOENIX – 441 West Geneva Drive Tempe, AZ 85282 Phone (602) 268-7901 Fax (602) 268-7909

OXNARD - 3441 Galaxy Place Oxnard, CA 93030 Phone (805) 485-0700

HONOLULU - 689 Kakoi Street 2-B Honolulu, HI 96819 Phone (808) 843-2000 Fax (808) 834-8000